



1" 5.6/35mm C		1"	2/3"	1/1.8"
FOCAL LENGTH		f=35mm		
MAX. DIAMETER (RATIO)		F=1:5.6~32		
ELEMENT AND GROUP		6 GROUPS 7 ELEMENTS		
FOCUSING RANGE		500mm - 250mm		
IMAGE SIZE		9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
FIELD OF VIEW (FOR Max.O.D. TARGET)	VER.	270.6mm	186.1mm	152.3mm
	HOR.	360.5mm	248.1mm	203.0mm
	DIA.	450.3mm	310.0mm	253.7mm
FIELD OF VIEW (FOR Min.O.D. TARGET)	VER.	76.6mm	52.6mm	43.0mm
	HOR.	102.3mm	70.2mm	57.4mm
	DIA.	128.3mm	87.8mm	71.8mm
TV DISTORTION (FAR)		0.07%		
TV DISTORTION (NEAR)		-0.25%		
FLANGE BACK		17.526mm in air		
BACK FOCUS		18.7mm in air		
FILTER THREAD SIZE		---		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 13.4mm REAR ϕ 10mm		
MOUNT		C-MOUNT		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 120L/mm CORNER 80L/mm		
LENS COATING		MULTI COATING		
WEIGHT		T.B.D.		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



SCALE 1/1	LM35HC-OPT
1" F5.6 f=35mm	
SPEC.SEET-1	